

Nitrile Glove

- Protection from unwanted or dangerous substances
- Beaded cuff makes donning easy and helps prevent roll back
- Superior strength with better puncture resistance
- Full textured enhances wet and dry grip
- Thinner gauge improves tactile sensitivity
- Custom design enhances comfort and fit
- Provide an alternative solution for individuals who are allergic to natural rubber latex



Quality Standards

- Conforms to ASTM D6319 and EN455 Standards
- Manufactured under QSR (GMP), ISO 9001:2015 and ISO 13485:2016 Quality Management System

Glove Sizes

- Extra-Small, Small, Medium, Large, Extra-Large
- Size of gloves shall be marked in the check box on the shipping carton with black ink

Product Specifications

- **Type:** Powdered & Powder-Free, Non-sterile
- **Material:** 100% Synthetic Nitrile Latex
- **Colour:** Blue, White, Black,
- **Design & Features: Powdered:**
- Ambidextrous, finger textured or palm textured surface, beaded cuff, USP grade absorbable cornstarch
- **Powder-Free:** Polymer coated or online single chlorinated, offline double chlorinated, ambidextrous, finger textured or palm textured surface, beaded cuff
- **Storage:** The gloves shall maintain their properties when stored in a dry condition. Avoid direct sunlight
- **Shelf-life:** 5 years from the date of manufacturing

International Quality Certificate Awarded:



Physical Dimensions

Dimensions	Standards		
	Top Glove	ASTM D3578	EN 455
Length (mm)	Min 230, Min 240, 300 ± 10	Min 220 (XS, S) Min 230 (M, L, XL)	Min 240
Palm Width (mm)			
• XS	76 ± 3	70 ± 10	≤ 80
• S	84 ± 3	80 ± 10	80 ± 10
• M	94 ± 3	95 ± 10	95 ± 10
• L	105 ± 3	110 ± 10	110 ± 10
• XL	113 ± 3	120 ± 10	≥ 110
Thickness : Single Wall (mm)			
• Finger	Min 0.05	Min 0.05	N/A
• Palm	Min 0.05	Min 0.05	N/A

Physical Properties

Property	ASTM D6319	EN 455
Tensile Strength (MPa)		
• Before Aging	Min 14	N/A
• After Aging	Min 14	N/A
Elongation at Break (%)		
• Before Aging	Min 500	N/A
• After Aging	Min 400	N/A
Median Force at Break (N)		
• Before Aging	N/A	Min 6
• After Aging	N/A	Min 6